





GW4060

LABORATORY GLASSWARE WASHER WITH DRYING SYSTEM
BASIC LINE - GLASSWARE WASHER 60 CM WITH DRYING SYSTEM

- ✓ washing up to 95°C antibacterical thermal disinfection
- ✓ electronic programming: 9 set programs + 6 free programs
- ✓ microprocessor programmable electronic control
- ✓ serial port RS232 for connection to external printer or PC
- ✓ forced hot air drying system with air filter 98% DOP
- ✓ alkaline powder detergent dispenser
- ✓ peristaltic pump for acid liquid neutralizer
- ✓ possibility of installing up to 2 additional peristaltic pumps
- ✓ washing chamber and internal door in AISI 316L stainless steel
- ✓ external panels made in AISI 304 stainless steel
- ✓ 2 independent washing levels through telescopic guides
- ✓ external dimensions LxWxH (mm) 600x605x850
- ✓ internal working dimensions LxWxH (mm) 520x515x545
- ✓ incorporated water softener with salt sensor

- cold water and demineralized water connections
- electronic door lock system for user safety
- ✓ electrical connection 3P+N 400V 50Hz 7kW max
- ✓ single phase version available 1/N/PE 230V 50Hz 2.8Kw max (GW4060-1)
- ✓ 60Hz version available
- ✓ without trolleys

BMM Weston Limited, Faversham, Kent, ME13 7 EB, ENGLAND Phone +44 (0) 1795 533441, Fax: +44 (0) 1795 538891, sales@bmmweston.co.uk

www.bmmweston.com

