



WD4060

WASHER DISINFECTOR WITH DRYING SYSTEM, EN 15883 APPROVED
BASIC LINE - WASHER DISINFECTOR 60 CM WITH DRYING SYSTEM

- ✓ Washing up to 95°C - antibacterial thermal disinfection
- ✓ Electronic programming: 9 set programmes + 6 free programmes
- ✓ Microprocessor programmable electronic control
- ✓ Serial port RS232 for connection to external printer or PC
- ✓ Forced hot air drying system with HEPA air filter
- ✓ High efficiency steam condenser Ecoslim, with cold water injection
- ✓ Peristaltic pump for liquid detergent and level sensor
- ✓ Peristaltic pump for acid liquid neutralizer and level sensor
- ✓ Possibility of installing 1 additional peristaltic pump
- ✓ Washing chamber and internal door in stainless steel AISI 316L
- ✓ External panels in stainless steel AISI 304
- ✓ External dimensions LxWxH (mm) 600x605x850
- ✓ Internal working dimensions LxWxH (mm) 520x515x545
- ✓ Incorporated water softener with salt sensor

- ✓ Cold water and demineralized water connections
- ✓ Electronic door lock system for user safety
- ✓ Electrical connection 3P+N 400V 50Hz 7kW max
- ✓ Single phase version available 1P+N 230V 50Hz 3.3kW max (code WD4060-1)
- ✓ Three phase without neutral version available 3P 400V 50Hz 7kW max (code WD4060-3)
- ✓ 60Hz version available
- ✓ Without trolleys
- ✓ 2 independent washing levels through telescopic guides available (code WD4060R)

BMM Weston Limited, Faversham, Kent, ME13 7 EB, ENGLAND
Phone +44 (0) 1795 533441, Fax: +44 (0) 1795 538891, sales@bmmweston.co.uk

www.bmmweston.com

